



NYLON REFLECTIVE

APPLICATION INSTRUCTIONS

STEP BY STEP

Step 1
Feed material into cutter



so that the matte side is face up.

Step 2
Design and cut your



graphic in reverse (mirror image).

Step 3
Weed away
excess



material using tweezers or weeding tool.

Step 4

Preheat your fabric and position weeded



image on shirt with Glossy side face up.

Step 5

Heat apply the material onto the shirt. See 2



shirt. See 2 step instruction. Do not use Teflon sheets when pressing.

Step 6
Peel Mylar
backing
warm.



Step 7: Repeat steps 1-6 after cool down.

APPLICATION

Nylon

Step 1 Step 2

First Press Repress After Cool Down

Press Time: 3-4 seconds 10-15 seconds

Temperature: 295-300°F (145-150°C) 295-300°F (145-150°C)

Pressure: Light to Medium Light to Medium

Suggested Blade: 45 degree N/A
Suggested Force: 120gf N/A
Peel: Warm Warm

Wash Temp.: N/A Up to 105°F (40°C)

Do not use Teflon sheets when pressing All technical information and recommendations are based on tests we have conducted. Users should conduct their own tests before proceeding

Notes

Recommended Fabrics

Nylon Flags Nylon Jackets

Accessories Required

Computer, Cutter, Heat Press, Heat Transfer Vinyl

Cutting Notes

You should always test cut prior to any production run. Cutter settings may need to be adjusted as your blade ages. For optimal cutting and weeding, maintain a line thickness of at least 0.5" for lettering & logos.

Care Instructions

Machine wash using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not iron directly onto this material. Wash Temperature should not exceed 105°F.

Storage

MultiCut Nylon Reflective has a 1 year shelf life when stored at room temperature. Keep away from direct heat, sunlight and humidity. Keep backing free of dust and other particles.

2-Step Heat Application

In order for Nylon to stick to the shirt fabric perfectly, it is necessary to repress the shirt a second time according to the instructions above.

