



ONE-4-ALLTM

APPLICATION INSTRUCTIONS

STEP BY STEP

Step 1
Feed the material into cutter so



that the matte side is face up.

Step 2
Design and cut your graphic in



reverse (mirror image).

Step 3 Weed away excess material



using tweezers or weeding tool.

Step 4
Preheat
your fabric
and position



and position weeded image on shirt with Glossy side face up.

Step 5
Heat apply the material onto the shirt. Press at 260°F for 3-5 seconds. Use medium pressure. Do not use Teflon sheets when pressing.

Step 6
Peel Mylar
backing
warm.



APPLICATION

Poly/Cotton Nylon

Press Time: 5 seconds 5 seconds, repress 10 seconds

Temperature: 260°F (125°C) 300°F (150°C)

Pressure: Medium Low
Suggested Blade: 45 degree 45 degree
Suggested Force: 120gf 120gf
Peel: Warm Warm

Wash Temp.: Up to $140^{\circ}F$ ($60^{\circ}C$) Up to $140^{\circ}F$ ($60^{\circ}C$)

Do not use Telfon sheets when pressing All technical information and recommendations are based on tests we have conducted.

Users should conduct their own tests before proceeding

Notes

Recommended Fabrics

100% cotton 100% polyester Poly/cotton blends Polyester knits Polyester mesh Poly/foam & cotton caps Nylon, Lyca, Spandex Satin

Accessories Required

Computer, Cutter, Heat Press, Heat Transfer Vinyl

Features

All Purpose Use - This vinyl is designed to be used on a wide range of materials including cotton, polyester, cotton/polyester blends and Nylon.

Dye Blocking - One-4-All has dye blocking ability to prevent any dye migration when printing onto 100% polyester.

Low Heat - In addition, due to the low heat application, this vinyl can be used on heat sensitive fabrics that may other wise burn or discolor during the application process.

Cutting Notes

You should always test cut prior to any production run. Cutter settings may need to be adjusted as your blade ages. For optimal cutting and weeding, maintain a line thickness of at least 1/8" for lettering & logos.

Care Instructions

Machine wash using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not iron directly onto this material. Wash Temperature should not exceed 140°F.

Storage

One-4-All has an indefinite shelf life when stored at room temperature. Keep away from direct heat, sunlight and humidity. Keep backing free of dust and other particles.

Multi Color Layering

When producing multi-colored designs, follow above instructions for each color (up to three colors). Repress shirt for 5 seconds with silicon sheet once layering is complete. Metallic Colors cannot be layered.