



LUSTRE

(Premium Reflective)

APPLICATION INSTRUCTIONS

STEP BY STEP

Step 1 Feed material into cutter



so that the matte side is face up.

Step 2 Design and cut your graphic in



reverse (mirror image).

Step 3 Weed away excess material



using tweezers or weeding tool.

Step 4
Preheat
your fabric
and position



weeded image on shirt with Glossy side face up.

Step 5 Heat apply the material onto the



shirt. Press at 310-330°F for 15 seconds. Use medium pressure. Do not use Teflon sheets when pressing.

Step 6
Peel Mylar
backing
warm.



instructions/reflect.pdf V.05182021

APPLICATION

Reflective

Press Time: 15 seconds

Temperature: 310-330°F (155-165°C)

Pressure: Medium
Suggested Blade: 45 degree
Suggested Force: 160gf
Peel: Warm

Wash Temp.: Up to $140^{\circ}F$ (60°C)

Do not use Teflon sheets when pressing All technical information and recommendations are based on tests we have conducted.

Users should conduct their own tests before proceeding

Notes

Recommended Fabrics

100% cotton 100% polyester Poly/cotton blends Polyester knits Polyester mesh Poly/foam & cotton caps Satin

Accessories Required

Computer, Cutter, Heat Press, Heat Transfer Vinyl

Cutting Notes

You should always test cut prior to any production run. Cutter settings may need to be adjusted as your blade ages. For optimal cutting and weeding, maintain a line thickness of at least 1/8" for lettering & logos.

Care Instructions

Machine wash using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not iron directly onto this material. Wash Temperature should not exceed 140F

Storage

MultiCut Lustre has an indefinite shelf life when stored at room temperature. Keep away from direct heat, sunlight and humidity. Keep backing free of dust and other particles

