



PAROPY INKJET DARK



APPLICATION INSTRUCTIONS

STEP BY STEP

Step 1

Feed material into inkjet printer so that the printer is printing on the printable side (white matte coated side). Use Plain Paper mode.

Step 2

Design your image and place your cut lines. Print and Cut your design right reading.

Step 3

Weed away excess material using tweezers or weeding tool.

Step 4

Prepress fabric for 5 seconds. Remove backing material and place on fabric with image face up. Place silicon sheet on top of image.

Step 5

Heat apply the material onto the shirt. Press at 375°F at 20-25 seconds. Use medium pressure.

Step 6

Peel silicon sheet cool.

APPLICATION

Printing Inks Dye & Pigment Inks Print Mode Plain Paper **Image** Right Reading Press Time: 20-25 seconds 375°F (190°C) Temperature: Pressure: Medium Suggested Blade: 45 degree Suggested Force: 40-75qf Peel: Cool

Wash Temp.: Up to $105^{\circ}F$ ($40^{\circ}C$)

All technical information and recommendations are based on tests we have conducted. Users should conduct their own tests before proceeding

Notes

Recommended Fabrics

Light or Dark Colored 100% cotton 100% polyester* (see note below) Poly/cotton blends* Poly/foam & cotton caps Satin

Accessories Required

Computer, Inkjet Printer, Heat Press. Cutter/Plotter Optional.

Printable side

The printable side (white matte coated side) where film peels off.

Cutting Notes

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as your blade ages. For optimal cutting and weeding, maintain a line thickness of at least 1/8" for lettering & logos.

Care Instructions

Wait 24 hours before washing. Machine wash using mild detergent. Do not use bleach or other aggressive cleaning agents. Cannot be dry cleaned. Wash Temperature cannot exceed 105°F.

Storage

Inkjet Dark has an indefinite shelf life when stored at room temperature. Keep away from direct heat, sunlight and humidity.

Non-Continuous Parts

This paper cannot be used with Tack. Try to design the material without any non-continuous parts. You can also hand place non-continuous parts on to your shirt.

*Some polyester garments may experience discoloration and/or dye migration, prior testing is strongly recommended